



SUBSTITUTE SPECIFICATION - MARKED UP COPY

TITLE: LCD OPTICAL WAVEGUIDE DEVICE

BACKGROUND OF THE INVENTION

5 (a) Field of the Invention

The present invention is related to an improved structure of a LCD optical wave-guide device, and more particularly to a backlight module free of dark ~~band~~ bands and bright ~~band~~ bands.

10 (b) Description of the Prior Art:

As illustrated in Fig. 1 of the accompanying drawings for a sectional view of the structure of a backlight module for an LCD of the prior art, the backlight module is essentially comprised of a reflector mask 10, multiple
15 light sources 20, a diffuser plate 30, a lower diffuser sheet 40, a prism 50, a reflective polarizing sheet or an upper diffuser 60 and a protector sheet 70 arranged in sequence from inside out. Wherein, ~~those~~ the light sources 20 may be each a light tube in the shape of a
20 stripe, U-shape or other ~~continuously~~ continuous curve ~~and~~ arranged at a proper spacing between the reflector mask 10 and the diffuser plate 30 and the ~~lights~~ light emitted by each of ~~those~~ the light sources 20 provide the display effects by the LCD. Therefore, the diffuser plate 30
25 functions to diffuse the ~~lights~~ light passing through it to correct the dark ~~band~~ bands and the bright ~~band~~ bands created on the LCD due to the absence of light produced at each spacing between two abutted sources 20.

Whereas the diffuser plate 30 functions only to help
30 achieve the even diffusion for ~~lights~~ light passing

through it, it has a limited efficiency in correcting the phenomenon of the bright ~~band~~ bands and the dark ~~band~~ bands observed on the LCD. An improvement is made for certain backlight modules by ~~having extended on purpose~~
5 extending the distance between ~~those~~ the light source 20 and the diffuser plate 30 in the hope of widening the scope of each of those light sources 20 entering into the diffuser plate 30 to achieve the purpose of reducing the dark ~~band~~ bands. However, the structural design for such
10 an improvement not only provides limited effects but also results in ~~that the~~ a backlight module which must be made thicker ~~to fail~~ thereby failing the compact requirements of the ~~in the~~ current LCD market.

STEP
Furthermore, some other backlight modules ~~seeks~~ seek
15 to provide extinction (dispersion) on the surface of the diffuser plate by printing on the diffuser plate with ink containing SiO₂ or TiO₂ to achieve the purpose of reducing the dark ~~band~~ bands. Again, the extinction process not only increases the production cost of the diffuser and the
20 complexity of the manufacturing process, but also relates to a passive solution to reduce the dark ~~band~~ bands on LCD since the extinction ~~is created~~ occurs only after the light lands on the surface of the diffuser.

25 SUMMARY OF THE INVENTION

The primary purpose of the present invention is to provide an improved structure of an optical wave-guide device to effectively solve the problem of the bright ~~band~~ bands and dark ~~band~~ bands on the LCD ~~of the LCD~~ and reduce
30 the spacing between light sources and a lower diffuser

sheet to make the backlight module thinner for ~~the~~ meeting. ✓
the compact requirements of the current LCD market by
replacing the diffuser plate with an optical wave-guide
device. To achieve the purpose, the optical wave-guide
5 device is provided between light sources and a lower
diffuser sheet for the ~~lights~~ light passing through the
optical wave-guide device to be properly refracted and
reflected to evenly diffuse via the lower diffuser sheet
in thereby providing an active solution.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a sectional view of the structure of a
backlight module of the prior art.

Fig. 2 is a sectional view of a backlight module of a
15 first preferred embodiment of the present invention.

Fig. 3 is a sectional view showing that the surface
of the optical wave-guide device of the present invention
is embossed on the surface facing a lower diffuser sheet.

Fig. 4 is a sectional view showing that the surface
20 of the optical wave-guide device of the present invention
is embossed on the surface facing multiple light sources.

Fig. 5 is a sectional view a sectional view showing
that the surface of the optical wave-guide device of the
present invention is embossed on the surface facing away
25 the lower diffuser sheet.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Fig. 2, a first preferred embodiment of
the present invention ~~is essentially comprised of the~~
30 backlight module ~~is essentially comprised of~~ having a

reflector mask 10, multiple light sources 20, a diffuser plate 30, a lower diffuser sheet 40, a prism 50, a reflective polarizing sheet ~~or (or an upper diffuser diffuser)~~ 60 and a ~~protector~~ protective sheet 70 arranged
5 in sequence from inside out. Wherein, ~~those~~ the light sources 20 may be ~~each~~ shaped as a light tube in a stripe shape, U-shape or other continuously ~~curve~~ curved shape. The light sources are preferably and arranged at a proper spacing between the reflector mask 10 and the lower
10 diffuser sheet and the ~~lights~~ light emitted by each of ~~those~~ the light sources 20 provide the display effects ~~by~~ for the LCD.

At least one optical wave-guide device 80 is separately provided between those light sources 20 and the
15 lower diffuser sheet 50. The optical wave-guide device 80 is made into a plate and provided with multiple recesses 81, ~~each to accommodate~~ accommodating a respective light source 20, ~~and the~~. The light emitted from each light source 20 ~~passing~~ passes through the optical wave-guide
20 device 80 and is refracted and reflected to, ~~thereby,~~ be evenly diffused via the lower diffuser sheet ~~to provide~~. As a result this preferred embodiment provides an active means to eliminate the bright ~~band~~ bands and dark ~~band~~ bands which otherwise ~~will~~ would be formed between any two
25 abutted light sources 20. Furthermore, replacing the diffuser plate of the prior art with the optical wave-guide device 80 reduces the spacing between the light source 20 and the lower diffuser sheet to further advantageously reduce the thickness of the backlight
30 ~~module in meeting compact requirements.~~

The optical wave-guide device 80 may be made of plastic materials including but not limited to Polycarbonate (PC), or Polymethyl methacrylate (PMMA), or Polyethylene Terephthalate (PET) in ~~to~~ a white or transparent stick structure, ~~or made of~~ transparent plastic materials, e.g. PC or PMMA added with diffusion agent (such as SiO₂ or TiO₂) in a white mat stick structure so to produce the optical wave-guide device 80 with various refraction effects for the selection of the proper optical wave-guide device 80 depending on the spacing between the backlight module and the light source 20.

Now referring to Fig. 3, at least one surface of the optical wave-guide device 80, is locally or entirely distributed with embossment 82 on the surface facing the lower diffuser sheet 40 in accordance with a second preferred embodiment of the present invention; or on the surface of the recess 81 ~~at~~ where the optical wave-guide device 80 is facing the light source 20 as illustrated in Fig. 4 in accordance with a third preferred embodiment; or on the surface of the optical wave-guide device 80 ~~at where~~ facing away from the lower diffuser sheet 40 as illustrated in Fig. 5 in accordance with a fourth embodiment. The embossment ~~made~~ forms at least one straight line or curve ~~or~~ (or the combination of ~~both~~ both) in ~~a~~ the form of V-, U-, or C-shaped cut for the convex of the embossment 82 to create a converging effect so as to evenly distribute the lights from the light source 20 ~~to diffuse~~ diffusing from the concave portion of each embossment 82, ~~thus~~ to thereby effectively solve the

problem of bright ~~band bands~~ and dark ~~band bands~~ observed with the ~~prior art LCD's~~ LCD of the prior art.

Alternatively, the same effects can be achieved by having at least one surface of the optical wave-guide device 80 locally or entirely matted, or printed with ink, or distributed with concave and convex points in either round, rectangular, diamond or polygonal form.

The preferred embodiments of the present invention by ~~providing~~ provide an improved structure of a backlight module to reduce the spacing between light sources and diffuser plate, ~~thus to~~ and thereby reduce the thickness of the backlight module ~~in meeting~~ allowing the production of a more compact LCD requirements is innovative and practical, and this application is duly filed for a utility pattern. It should be noted that the specification and drawings are provided ~~as one of~~ to describe the preferred embodiments of the present invention and do not in any way limit the present invention. Therefore, any structure, device, and/or characteristics similar or equivalent to that of the present invention shall be deemed as falling within the scope of the purpose and claims made by the present invention.